

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020	Revision: 24.03.2020
SECTION 1: Identification of the substance/mixture and of the	e company/undertaking
· 1.1 Product identifier	

- · Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: Betek Boya ve Kimya Sanayi A.S.
G.O.S.B. Tembelova Alani 3200 Sokak No:3206
41400 Gebze/ Kocaeli/ Türkiye
Tel: 00 90 262 678 30 00
Fax: 00 90 262 641 21 68
murat.kucukkul@betek.com.tr

- Further information obtainable from: R&D Department
- 1.4 Emergency telephone number: 0090 262 678 30 00

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 1B	H350	May cause cancer.
Repr. 1A	H360Df	May damage the unborn child. Suspected of damaging fertility.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07 Skin Irrit. 2

H315 Causes skin irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB –

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA (Contd. of page 1) · Hazard pictograms GHS07 GHS02 GHS08 GHS09 · Signal word Danger · Hazard-determining components of labelling: toluene Lead sulfochromate yellow naptha(petroleum), hydrotreated heavy Solvent naphtha (petroleum), medium aliph. · Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H350 May cause cancer. H360Df May damage the unborn child. Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. *H304* May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. *P301+P310* IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P321 Specific treatment (see on this label). P331 Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Take off contaminated clothing and wash it before reuse. *P362+P364* P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. • Additional information: Contains 2-butanone oxime. May produce an allergic reaction.

· 2.3 Other hazards

- Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description:

cosolvent Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2,	≤ 2.5%
O Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2,	
H315; Eye Irrit. 2, H319	
(Contd. o	on page 3

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA

	(Conto	l. of page 2)
CAS: 7727-43-7	barium sulphate, natural	25-50%
EINECS: 231-784-4	EINECS: 231-784-4 substance with a Community workplace exposure limit	
CAS: 1330-20-7	xylene	10-25%
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 108-88-3	toluene	10-25%
EINECS: 203-625-9	Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 1344-37-2	Lead sulfochromate yellow	2.5-10%
EINECS: 215-693-7	Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 96-29-7	2-butanone oxime	≤ 2.5%
EINECS: 202-496-6	Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317	
·SVHC	·	
1344-37-2 Lead sulf	fochromate yellow	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- *After swallowing: If symptoms persist consult doctor.*
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

GB

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA

(Contd. of page 3)

 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

 • 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents

- 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

\cdot Ingredients with limit values that require monitoring at the workplace:	
7727-43-7 barium sulphate, natural	
WEL Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust	
1330-20-7 xylene	
WEL Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV	
108-88-3 toluene	
WEL Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk	
	(Contd. on page 5

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA

(Contd. of page 4) 1344-37-2 Lead sulfochromate yellow WEL Long-term value: 0.05 mg/m³ as Cr; Carc, Sen 111-76-2 2-Butoxyethanol WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV Ingredients with biological limit values: 1330-20-7 xylene BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid 1344-37-2 Lead sulfochromate yellow BMGV 10 µmol/mol creatinine Medium: urine Sampling time: post shift Parameter: chromium 111-76-2 2-Butoxyethanol BMGV 240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid • Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin. • Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA

(Contd. of page 5)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Tightly sealed goggles

9.1 Information on basic physical and chemical properties		
General Information Appearance:		
Form:	Fluid	
Colour:	According to product specification	
Odour:	Characteristic	
Change in condition Initial boiling point and boiling	range: Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gas):	Not applicable.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
Density at 20 °C:	1.45 g/cm ³	
Solubility in / Miscibility with		
water:	Not determined.	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA

(Contd. of page 6)

LD/LC50 values relevant for classification:				
1330-20-7 xylene				
Oral	LD50	4300 mg/kg (rat)		
Dermal	LD50	2000 mg/kg (rabbit)		
108-88-3 toluene				
Oral	LD50	5000 mg/kg (rat)		
Dermal	LD50	12124 mg/kg (rabbit)		
Inhalative	LC50/4 h	5320 mg/l (mouse)		
1344-37-2 Lead sulfochromate yellow				
Oral	LD50	>10000 mg/kg (rat)		
Primary ir	ritant effe	ct:		
Skin corro	sion/irrita	tion		
Causes skin irritation.				

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity
- May cause cancer.
- · Reproductive toxicity
- May damage the unborn child. Suspected of damaging fertility.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard
- May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 8)

Preparation date: 24.03.2020

Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA

(Contd. of page 7)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• *Recommendation:* Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR	1263 PAINT, ENVIRONMENTALLY HAZARDOUS, specia provision 640D
IMDG IATA	PAINT (Lead sulfochromate yellow), MARINE POLLUTANT PAINT
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F1) Flammable liquids. 3
IMDG	
Class	3 Flammable liquids.
Label	3
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Lea sulfochromate yellow
Marine pollutant:	Yes Symbol (fish and tree)

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA

	(Contd. of page
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN1263, PAINT, special provision 640D
-	ENVIRONMENTALLY HAZARDOUS, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 28, 30, 47, 48, 72
- · National regulations:

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

1344-37-2 Lead sulfochromate yellow

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

(Contd. on page 10)

GB -

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ İDEAL ENDÜSTRİYEL BOYA

(Contd. of page 9) H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H350 May cause cancer. H351 Suspected of causing cancer. H360Df May damage the unborn child. Suspected of damaging fertility. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 1B: Carcinogenicity - Category 1B Carc. 2: Carcinogenicity - Category 2 Repr. 1A: Reproductive toxicity - Category 1A Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 GB