

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Preparing date 02.02.2017

Revision: 02.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Fawori Akrilik Sprey RAL9005 Parlak Siyah
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Acrylic spray paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
COLORPACK s.r.l.
Via B.Cellini 26, 20020 Solaro, Milano - Italia
Faks +39 029691714 Tel. +39 029690664 (8.30-17.00 from Monday to Friday)
Web sitesi: www.colorpack.com
e-mail: info@colorpack.com
- **Further information obtainable from:** R&D Department
- **1.4 Emergency telephone number:**
COLORPACK s.r.l. Tel. +39 029690664 (8.30-17.00 from Monday to Friday)
Medikal: Centro Antiveneni di Milano - Azienda Ospedaliera Niguarda Cà Granda - Tel. 02/66101029

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
acetone
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.

(Contd. on page 2)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Preparing date 02.02.2017

Revision: 02.02.2017

Trade name: Fawori Akrylic Sprey RAL9005 Parlak Siyah

(Contd. of page 1)

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**· **Description:**· **Dangerous components:**

	cosolvent ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤ 2.5%
CAS: 67-64-1 EINECS: 200-662-2	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 68476-40-4 EINECS: 270-681-9	Hydrocarbons, C3-4 ⚠ Flam. Gas 1, H220; Press. Gas C, H280	25-50%
CAS: 1330-20-7	Xylol, Isomerengemisch (wenn Flammpunkt < 21 °C) ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-10%
CAS: 110-82-7 EINECS: 203-806-2	cyclohexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	≤ 2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

GB

(Contd. on page 3)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Preparing date 02.02.2017

Revision: 02.02.2017

Trade name: *Fawori Akrylic Sprey RAL9005 Parlak Siyah*

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Preparing date 02.02.2017

Revision: 02.02.2017

Trade name: Fawori Akrylik Sprey RAL9005 Parlak Siyah

(Contd. of page 3)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility: Not required.**

· **Further information about storage conditions:**

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **7.3 Specific end use(s) No further relevant information available.**

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities: No further data; see item 7.**

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

1330-20-7 Xylol, Isomerengemisch (wenn Flammpunkt<21 °C)

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk, BMGV

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

111-76-2 2-Butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm
Long-term value: 123 mg/m³, 25 ppm
Sk, BMGV

· **Ingredients with biological limit values:**

1330-20-7 Xylol, Isomerengemisch (wenn Flammpunkt<21 °C)

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

111-76-2 2-Butoxyethanol

BMGV 240 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: butoxyacetic acid

· **Additional information: The lists valid during the making were used as basis.**

(Contd. on page 5)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Preparing date 02.02.2017

Revision: 02.02.2017

Trade name: **Fawori Akrilik Sprey RAL9005 Parlak Siyah**

(Contd. of page 4)

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

· Odour: Characteristic

· Change in condition

Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: < 0 °C

· Ignition temperature: >400 °C

· Danger of explosion: Not determined.

· Explosion limits:

Lower: 1.8 Vol %

(Contd. on page 6)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Preparing date 02.02.2017

Revision: 02.02.2017

Trade name: Fawori Akrilik Sprey RAL9005 Parlak Siyah

(Contd. of page 5)

Upper:	9.5 Vol %
· Vapour pressure at 20 °C:	4.5 bar
· Density at 20 °C:	0.95 g/cm ³
· Vapour density at 20 °C	>1 g/cm ³ (hava=1)
· Solubility in / Miscibility with water:	Partly miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	600 g/l
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity:

· LD/LC50 values relevant for classification:

110-82-7 cyclohexane

Oral	LD50	12705 mg/kg (rat)
------	------	-------------------

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitisation: No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 7)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Preparing date 02.02.2017

Revision: 02.02.2017

Trade name: Fawori Akrylic Sprey RAL9005 Parlak Siyah



(Contd. of page 6)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | <p style="text-align: center;">UN1950</p> |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | <p style="text-align: center;">1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable</p> |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR | <div style="text-align: center;">  </div> <p style="text-align: center;">Class 2 5F Gases.
Label 2.1</p> |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center;">  </div> <p style="text-align: center;">Class 2.1
Label 2.1</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | <p style="text-align: center;">Void</p> |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | <p style="text-align: center;">No</p> |

(Contd. on page 8)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Preparing date 02.02.2017

Revision: 02.02.2017

Trade name: Fawori Akrilik Sprey RAL9005 Parlak Siyah

(Contd. of page 7)

· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - National regulations:
- | Class | Share in % |
|-------|------------|
| NK | 55.5 |
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 9)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Preparing date 02.02.2017

Revision: 02.02.2017

Trade name: Fawori Akriik Sprey RAL9005 Parlak Siyah

(Contd. of page 8)

· **Contact:**

Murat Küçük / TSE - Safety Data Sheet preparer certified.

The certificate ID and date of the document: GBF-A-0-2289 / 23.03.2016

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

GB